



**WWT
International**

HYDROHAMMER™

**Extended-reach tool rugged enough to survive the toughest wellbores,
all while minimizing damage to other BHA components and coiled tubing.**



- Applies true pull force to the end of a coiled tubing string delivering industry leading reach.
- Adjustable pulse rate to optimize performance with other downhole tools.
- Operates dependably in wellbores with excessive debris and recirculated fluids.
- Compact and rugged.
- Eliminates the need for costly friction-reducing chemicals.
- Improves circulation, reduced or eliminates short trips.

Outside Diameter	2 7/8 in. and 3 1/8 in.
Connections	2 3/8 PAC or REG
Axial Force	Up to 6,000 lbf
Length	2.5 ft.
Flow Range*	1-7 BPM
Max Temperature	482°F (220°C)
Pressure Drop*	50-400 psi
Max Torque	2 7/8: 2,500 ft-lbf 3 1/8: 3,650 ft-lbf
Max Overpull	2 7/8: 103,000 ft-lbf 3 1/8: 137,600 ft-lbf

*Based on tool configuration

WWT International supports your operations from start to finish with full-service onsite mobilization and support 24/7. To find out more, visit our web site.



**WWT
International**

www.wwtco.com



Houston, Texas, USA · Midland, Texas, USA · Anaheim, California, USA · Aberdeen, Scotland · Al Khobar, KSA
Dubai, UAE · Abu Dhabi, UAE · Singapore · Quito, Ecuador